

ICI | FM 640 P-Series



www.infraredcamerasinc.com | sales@infraredcamerasinc.com

INFRARED CAMERAS INC.
2105 W. Cardinal Dr.
Beaumont, TX 77705

Phone: (409) 861-0788
Toll Free: (866) 861-0788

We are IR™

ICI | FM 640 P-Series

The ICI FM 640 P-Series is an uncooled FPA thermal imaging camera system which features ultra-high resolution in 640x480 pixels. The FM 640 features accurate temperature measurement, 2x & 4x Digital Zoom, up to 8 channels, and can save by RAW, AVI and CSV formats. The FM 640 is suitable for a wide variety of applications including electrical inspections, petrochemical, iron and steel, scientific research, fire-fighting, building inspections, process control, medical, veterinarian and more. Optional high temperature calibration available up to 500 °C.

Features

- Color Alarm (Isotherm)
- Recording Video Clip (AVI)
- Hot/Cold Spot Tracker
- Various Color Palettes
- Ethernet (RJ 45)
- 2x & 4x Digital Zoom
- 8 Channels

Specifications

- **Detector Array:** Uncooled FPA
- **Pixel Resolution:** 640x480
- **Spectral Band:** 8 μm to 14 μm
- **Thermal Sensitivity (NETD):** < 0.075 °C at 30 °C (75 mK)
- **Frame Rate:** 30 Hz P-Series
- **Dynamic Range:** 14-bit
- **Temperature Range:**
Standard: -20 °C to 120 °C
Optional: 0 °C to 500 °C
- **Operation Range:** -15 °C to 50 °C
- **Storage Range:** -40 °C to 70 °C
- **Analog Output:** NTSC
- **Video:** RAW, AVI, and CSV
- **Accuracy:** $\pm 2^\circ\text{C}$
- **Pixel Operability:** > 99 %
- **Dimensions (without lens):** 183 x 78 x 68 mm (H x W x D $\pm .5\text{mm}$)
- **Weight (without lens):** 500 g
- **Battery:** DC 12V : 5 W
- Ethernet

Applications

- Insulation Inspections
- Scientific Research
- Predictive Maintenance
- Reliability Engineering
- Medical Imaging
- Robotics
- HVAC
- Security
- Electrical

Lens & Software Options

- Outdoor Housing Germanium Window
- Encapsulation: IP 66 (optional)
- 500 °C High Temp. Mode (optional)
- Motorized (optional)
- Athermalized (optional)
- Optic Zoom lens (optional)

